




ZLIN
河南中铄重工集团

ZLIN
河南中铄重工集团

Henan Zlin Heavy Industry Group Co.,Ltd.

 河南省郑州市金水区花园路122号
No. 122, Huayuan Road, Jinshui District,
Zhengzhou City, Henan Province

 E-mail: alina@zlin-ind.com
电子邮件: alina@zlin-ind.com

 China: +86 136 7362 2363 (Wechat)
Philippines: 0977 4829 633 (Viber)

STATIONARY BATCHING PLANT



Whole Station	Model	HZS25	HZS35	HZS50	HZS60
	Max.productivity (m3/h)	25	35	50	60
	Standard discharge height	2	2	3.8	3.8
	Aggregate conveying type	Skid Hopper	Skid Hopper	Skid Hopper	Skid Hopper
	Total Power (KW)	50.25	75	111	105
	Site dimension(M)	12*20M	12*20M	12*20M	15*60M
	control type	Pneumatic + PLC	Pneumatic + PLC	Pneumatic + PLC	Pneumatic + PLC
	control system brand	Bosure-Schneider	Bosure-Schneider	Bosure-Schneider	Bosure-Schneider
Mixer part	Model	JS500	JS750	JS1000	JS1000
	Working cycle time(S)	72	72	60	60
	Mixing Power (KW)	18.5	30	37	37
Batching machine part	Model	PLD800	PLD1200	PLD1600	PLD1600
	Batchable number of aggregate	2	2-3	2-4	3-4
	Hopper capacity(m³)	2	2.2	3.7	3.7
	Power(Kw)	3*3	3*3	4*3	4*3
Weighing accuracy	Feeding height (mm)	2300	2800	3000	3000
	Aggregate	±2%	±2%	±2%	±2%
	Concrete,Water and Additive	±1%	±1%	±1%	±1%

STATIONARY BATCHING PLANT



Whole Station	Model	HZS75	HZS90	HZS120	HZS180	HZS240
	Max. productivity (m ³ /h)	75	90	120	180	240
	Standard discharge height	3.8	3.8	3.8	4.5	4.5
	Aggregate conveying type	Skid Hopper	Belt Conveyor	Belt Conveyor	Belt Conveyor	Belt Conveyor
	Total Power (KW)	110	145	210	268	363
	Site dimension(M)	12*20M	15*60M	15*60M	70*20M	80*30M
	control type	Pneumatic + PLC	Pneumatic + PLC	Pneumatic + PLC	Pneumatic + PLC	Pneumatic + PLC
	control system brand	Bosure-Schneider	Bosure-Schneider	Bosure-Schneider	Bosure-Schneider	Bosure-Schneider
	Mixer part	Model	JS1500	JS1500	JS2000	JS3000
Working cycle time(S)		60	60	60	60	60
Mixing Power (KW)		2*22	2*22	2*37	2*55	2*55
Batching machine part	Model	PLD2400	PLD2400	PLD3200	PLD4800	PLD6400
	Batchable number of aggregate	3-4	3-4	4	4	4
	Hopper capacity(m ³)	7	7	12	20	25
	Power(Kw)	11	11	11	15	15
	Feeding height (mm)	3200	3200	3500	3800	3800
Weighing accuracy	Aggregate	±2%	±2%	±2%	±2%	±2%
	Concrete,Water and Additive	±1%	±1%	±1%	±1%	±1%

DRUM TYPE MOBILE/PORTABLE BATCHING PLANT

Model	DHZS-30
Capacity	18-30m ³ /h
Mixer	JZM500 (0.5m ³)
Mixing Period	50-60s
Discharging Height	1.1m
Batcher	2-3 bins x 4m3
Feeding Height	2.94m
Cement Weighing System	300kg
Additive Weighing System	25kg
Horizontal Cement Silo(optional)	50ton
Screw Conveyor(optional)	219x8mx11kW
Dimension and Weight	7280x3350x1500; 8T
Chassis Size(LxW)	5740x1500mm
Tyres	765mm
Control System	Semi Auto with Control Panel
Total Power	15kw



DIESEL MIXING PUMP

Name	Manufacturer
Main oil pump	KAWASAKI
Hydraulic Rubber Pipe	ITALY MANULI
Sealing	PARKER
Electric Control System	SCHENIDER
Intermediate Relay	OMRON
Switch	GERMAN
Valve	HUADE(China best brand)
Pressure Meter	GERMAN
Button	SCHENIDER



PERFORMANCE	JBS40R	RATED DISCHARGE CAPACITY OF MIXER (M ³)	0.45
Theoretical conveying capacity (m ³ /h)	40	Hopper volume (L)	400
CONCRETE DELIVERY PRESSURE (MPA)	10	OUTLET DIAMETER (MM)	150
Maximum conveying distance (m) vertical/horizontal	100/500	Maximum aggregate particle size (mm)	40
DIESEL ENGINE POWER (KW)	82	LXWXH(MM)	5800x2200x3150
Conveyor cylinder bore x stroke (mm x mm)	180x1000	HOST MASS (KG)	6800
FUEL TANK VOLUME (L)	350	Rated feed capacity of mixer (m ³)	0.56

DIESEL TRAILER PUMP



Performance	HBTS40R	HBTS60R	HBTS80R	HBTS90R
Theoretical conveying capacity (m ³ /h)	53/29	61/38	98/59	92/55
Concrete delivery pressure (MPa)	12/6	12/7	12.5/7.5	9/16
Maximum conveying distance (m) vertical/horizontal	150/500	150/600	150/600	160/700
Diesel engine power (kW)	66	82	129	140
Conveyor cylinder bore x stroke (mm x mm)	160x 1300	180 x 1300	200 x 1650	200 x 1800
Main cylinder bore x stroke (mm x mm)	100 x 1300	110 x 1300	125 x 1650	140 x 1800
Fuel tank volume (L)	90	90	150	150
Upper hopper volume (m ³)	0.6	0.7	0.8	0.8
Feeding height (mm)	1250	1300	1450	1450
Outlet diameter (mm)	125	150	180	180
Maximum aggregate particle size (mm)	40	40	50	50
Dimension	4800 X 1750 X 1900	4800 X 1750 X 1900	6000 X 2000 X 2200	6000 X 2000 X 2200
Host mass (kg)	3500	4200	5800	6500

BOOM PUMP

We can provide chassis of SITRAK, Sino-Trunk, HOWO and Dongfeng.
We offer boom pump of 13m, 26m, 30m, 33m, 38m, 40m, 42m, 45m, 47m, 50m, 58m.

For detailed parameters please refer to the quotation



THREE-WHEEL MIXER TRUCK

Overall dimensions (length width height)	5200*1900*2600mm
Chassis rear axle	WuZheng
Engine model	32 hp diesel engine
Tire	700-16
Speed	High and low speed
Brake	Storage spring brake
Tank volume	2-2.5m ³
Tank material	High manganese steel
seal head	Forge and press
Tank reducer	KeYi
Hydraulic system	DaLi



Weight

3t

TRANSIT MIXER

5m³,6m³,8m³,10m³,12m³transit mixer are available.

Truck brand: Sinotruk, Howo, Dongfeng brand are available.



SELF LOADING MIXING TRUCK



Product Name	1.2 M ³	1.8 M ³ (270°)	2.6M ³ (270°)	3.5M ³ (270°)	4M ³ (290°)	5.5M ³ (270°)	6.5M ³ (290°)
Model	YUNNEI 490	YUNNEI 490	YUCHAI 4102	YUCHAI 4105	YUCHAI 4108	FAW XICHAI 6110	WEICHAI DEUTZ 6150
Dimensions	7300*1800*3450	7300*2650*3750	7100*2750*4100	7830*2680*4170	7640*2870*4750	8450*3100*4580	8450*3050*4830
Wheelbase (mm)	2560mm	2600mm	2650mm	2900mm	2480	3350	2850
Curb weight(kg)	4920	6000	7800	7800	9000	11200	12520
Drive Form	Torque converter	Torque converter	Torque converter	Torque converter	Torque converter	Torque converter	Torque converter
Maximum Speed (km/h)	30 km/h	30km/h	30km/h	30km/h	35km/h	42km/h	40km/h
Maximum Climbing Degree (°)	30°	30°	30°	30°	45°	45°	45°
Minimum Turning Radius (mm)	4700 MM	5270MM	5300MM	5300MM	4800MM	6200MM	4800MM
Minimum Ground Clearance (mm)	280 mm	280mm	380mm	380mm	330mm	380mm	350mm